

SKYJACK

SJ68/32 RT

ROUGH TERRAIN SCISSORS



CE
EU/ENG/03/2019

Dimensions	SJ6832 RT
A Work Height	11.75 m
B Raised Platform Height	9.75 m
C Lowered Platform Height	1.37 m
D Overall Width	1.76 m
E Overall Length	3.35 m
F Stowed Height (Rails Up)	2.51 m
G Stowed Height (Rails Down)	1.75 m
H Platform Width (Inside Dimension)	1.42 m
I Platform Length (Inside Dimension)	2.44 m
Specifications	SJ6832 RT
Extension Deck	1.52 m
Ground Clearance	0.20 m
Wheelbase	2.04 m
Weight	3,781 kg
Gradeability	40%
Turning Radius (Inside)	1.52 m
Turning Radius (Outside)	3.96 m
Lift Time (With Rated Load)	39 sec
Lower time (With Rated Load)	36 sec
Drive Speed (Stowed)	6.1 km/h
Drive Speed (Raised)	0.6 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	454 kg
Distributed Capacity (Main Platform)	318 kg
Distributed Capacity (Extension Deck)	136 kg
Local Floor Load (With Rated Load)	1248 kPa
Overall Floor Load (With Rated Load)	14 kPa
Maximum # of Persons (indoor/outdoor)	4/4 (to 7.92m) 2 (to 9.75m)
Tyre Type	Foam Filled
Tyre Size	26 x 12

- Drivable at full height with roll out deck fully extended
- Crossover symmetrical 4WD
- Multiple wet disc spring applied hydraulic release brakes
- 1.52 m Roll out extension deck
- 24hp Kubota Diesel engine
- 90° Swing out engine tray
- Relay-based control system
- SKYCODED™ Colour coded and numbered wiring system
- Up to 50% Gradeability
- Foam-filled grip lug tyres
- Wiring for AC outlet on platform
- Tilt alarm with drive & lift cut-out
- Overload sensing system
- Lowering warning system
- Operator horn
- Hinged railing system
- Full height spring hinged gate at rear of unit
- Lanyard attachment point
- Scissor guards
- Forklift pockets and tie down/lift lugs
- Independent/auto leveling outriggers
- Diesel engine with scrubber
- Flashing light
- Shroud-style control box guard
- 2.0kW Hydraulic generator
- Foam-filled grip lug non-marking tyres
- All motion audible alarm
- Secondary Guarding Lift Enable (SGLE)
- ELEVATE telematics